



MCM5

Description

The Conlux® MCM5 coin changer provides increased tube capacity, additional float options, and enhance product durability and aesthetics. A single-piece coin door provides better visibility of the coin path. The keypad and improved labeling makes it faster and easier to program the device.

Operators will also appreciate the third diagnostic LED light on the discriminator to “flag” maintenance needs. At the MCM5 coin changer, we are defining simple and delivering value.



COIN CHANGER

Benefits

Energy saving. 30% less power wasted while in idle state than other comparable models

Speed transactions and increase throughput. Quick coin payout simultaneously delivers up to 3 coins at

User-friendly operation. Redesigned 9-button keypad, tool-free access, and back or top-fill tube loading op

Automatic cassette programming. Avoid unintentional errors when using the preconfigured coin cassettes

Superior technology. Diversion path designed to resist salt water, vandalism, and damage



COIN CHANGER

Specifications

Coin Payout

- 5 coins

Coin Diameter

- 15mm - 28.5mm

Coin Thickness

- 1.3mm - 3.0mm

Input speed

- 1.5 coins per second

Output Speed

- 3 coins per second

Operating Temperature

- -15°C to 60°C

Power Requirements

- 34 V DC = MDB



COIN CHANGER

Tube/coin Level Recognition System

- Optical, Sonar

Support Tools

- N/A

Audit

- N/A