





CX25TM

Description

The CX25[™] is a robust coin dispenser offering years of reliable service and outstanding performance in h environments. Located at most self-service and self-checkout applications, this coin dispenser accommodate volumes of coin-typically up to 1,046 transactions before the CX25 requires refilling. This unit is available different bin configurations to fit a variety of envelopes.

When looking for an effective coin management solution, think of the CX25 for optimized performance wit life cycle. Ideal for banking and financial services applications like Multi-function ATMs and Money Transfer





Benefits

Low-maintenance efficiency. High capacity hopper requires less frequent fills minimizing downtime

High level of security. History of dispensed coins logged in firmware memory

Efficient and easy. Tilting bins for simple loading and emptying for effective cash management

Flexible design configurations. Four models to choose from: 3, 4, 6, or 8-bin hopper







Specifications

Coin Speed (coin/s)

• Depends on bin configuration

Dimensions (H x W x D mm)

- 3-Bin in-line: 231.1mm x 175.26mm x 264.1mm (without cup)
- 4-Bin in-line: 231.1mm x 175.26mm x 347.9mm (without cup)
- 6-Bin face-to-face: 231.1mm x 345.4mm x 264.1mm (without cup)
- 8-Bin face-to-face: 231.1mm x 348.74mm x 344.42mm (without cup)

Coin capacity

• Varies by bin configuration. 4-Bin configuration, maximum \$387.00 USD

Installation

· Device needs a host machine

Interfaces supported

RS232 serial port, USB connectivity

Power requirements

• Direct connection requires 24 V DC and 1.7 Amps maximum, External switching power supply: single 24 V I

Compliance

• CE, UL, CUL listed, RoHS





Variants



CX25 Bin Configurations

- 3-Bin System
- 4-Bin System
- 6-Bin System
- 8-Bin System



Accessories



Bins

Can be ordered separately

