

G-13.mft 3.5" coin validator

Most flexible and secure
coin validator



Gaming
Transportation
Vending
Retail

Perfect validation security

Anti-stringing protection and protocol
encryption for high manipulation security

Unique MFT coin validation technology for
highest coin security

Highly flexible through multiple models,
interfaces and sorters

CRANE



CRANE

PAYMENT SOLUTIONS

Crane Payment Solutions GmbH · Zum Fruchthof 6 · 21614 Buxtehude · Germany
Phone +49(0)41617290 · Fax +49(0)4161729115 · Web info@craneps.com · www.craneps.com

Most flexible and secure coin validator

G-13.mft 3.5" coin validator



The NRI G-13.mft sets the industry standard. By using the unique MFT validation technology upmost coin security is guaranteed. The G-13.mft has high flexibility through different models, interfaces and sorters.

High security:

- Highest coin validation security using the unique MFT Multi-Frequency Technology
- Detection of coin material by three coil pairs together with proven optical diameter measurement
- Simultaneous evaluation of 24 measurement parameters for 32 coin channels
- Protection against string manipulation
- Optical monitoring of coin path

Flexibility:

- Inhibit of single coins or coin groups via DIL switch
- Teach function for up to 8 coins/tokens as standard
- Powerful WinEMP software for downloading complete device and coin configuration
- On-site tool HENRI+ to easily update coin and configuration data sets as well as firmware

Versatility:

- Multiple machine interfaces available
 - serial S1
 - serial MDB
 - ccTalk, also via USB connection
 - parallel, also binary or serial impulses
 - SGI (Simple Gaming Interface) with fast coin acceptance for Casino applications


Accessories:

- Midi and Mini front plate
- Wake-up sensor for low-power applications
- 3-way sorter standard s² SSD-3001/2/3/4
- 3-way high speed sorter s² HSD-3000

Technical data:

Dimensions:	Height 102-mm, Width 89-mm, Depth 52-mm
Coin diameter:	15 - 31.5-mm (option up to 32.5-mm)
Coin thickness:	1.5 - 2.5-mm (option up to 3.3-mm)
Temperature:	-25°C up to +70°C
Power supply:	12 - 24-V DC ± 10% (optional: 10 - 48-V DC)

With the NRI G-13.mft you can relax – your machine is working with the best in class coin validation technology.



MFT Technology



HENRI+ service tool



USB interface



Frontplates



3-way sorter



3-way high-speed sorter

